



The **Multiverse**[®] **Node 2.4GHz** is the first building block of the Multiverse system.

Each **Multiverse**[®] **Node 2.4GHz** is a transceiver. As a single universe transmitter, it functions in a similar plug and play manner to the Multiverse[®] SHoW Baby[®] and legacy SHoW DMX SHoW Baby[®] products, but contains a 2.4GHz radio and full user interface, with four buttons and a backlit LCD display.

As a receiver, the **Multiverse Node** is the primary single universe standalone receiver in the Multiverse system, and can be part of a larger multi-universe setup.



What's in the box



Multiverse[®] Node 2.4GHz

SPECIFICATIONS:

P/N	Frequency	Universes
5903	2.4GHz	1
Physical		
Length	102.8mm (4.05 in)
Width	60mm (2.36 in)
Height	36.47mm (1.44 in)
Antenna	3dBi	
User Interface	4 Button/Backlit LCD display	
Construction	Die Cast Aluminum, Black	
Power Connector	Locking DC Jack, 5.5mm x 2.1mm, center positive, 12.1mm mating depth*	
Electrical		
Power	5-30VDC, 1W	
Broadcast Power	3.2mW, 10mW, 32mW, 100mW	
Broadcast Modes	Adaptive, Full, Low, Mid, High, Max	

Broadcast Modes	Maapuve, Full, Low, Mid, High, Max
DMX Burst Modes	Auto Dynamic
Ethernet Protocols	N/A
SHoW IDs	Multiverse: 217; Neo: 70
RF Sensitivity	-95dBm
RDM Features	RDM Proxy, RDM Responder

Product Information

Use Environment	Indoor
IP Rating	IP50
Compliance	FCC, IC, CE
Warranty	One year

*Note: This power supply connector is not compatible with SHoW Baby.

