Certificate of Wire Ropes

Name and address of manufacturer / EU-AR: Highlite International B.V.

Vestastraat 2, 6468EX Kerkrade **Netherlands**



THIS CERTIFICATE IS ISSUED UNDER THE SOLE RESPONSIBILITY OF:

Name and address of manufacturer: Highlite International B.V.

> Vestastraat 2, 6468EX Kerkrade Netherlands

Product identification: Safety 4mm, 100cm, Black, BGV-C1

71711

THE PRODUCT MENTIONED IN THIS CERTIFICATE HAS THE FOLLOWING PARAMETERS:

Finishing of rope ends 2 x thimble loops, 1 x master link

Other used parts of complete gear

Working load limit (WLL) 0.00 ton

Dimensions

Nominal wire rope diameter: 4,00 mm Length of wire rope: 1,00 m

Construction

Number of strands x number of wires + cores:

6 x 19 fiber core Direction and type of lay: Right regular lay

Preformed: Yes

Material

Tensile grade: 1960 N/mm2 Surface finishing of wires: Galvanized dry

Strength (BL)

Minimum breaking strength of wire rope: 9,63 kN Application Safety Wire rope manufactured according to standard: EN 12385

IMPORTANT: Max. load 15 kg according to BGV-C1

> Max. drop height object 20 cm Not suitable for lifting applications

The undersigned certifies on behalf of his company, that above particulars are correct and that the described wire rope is in compliance with the requirements of EC Machinery Directive 2006/42/EC.

SIGNED FOR AND ON BEHALF OF:

Place and date of issue: Kerkrade, 8 October 2021

Signature:

Name, function: Huub de la Haije, CEO

Highlite International B.V. Company name: