

# picklePATT™

Following the series of retro style lighting, the picklePATT is the new cute compact addition to our tungsten classic family.

It is the second fixture, made in collaboration with lighting designer Tim Routledge, which combines traditional aesthetics and modern build quality. The picklePATT is specifically designed to further the current trend for tungsten eye-candy on stage and set - for bands, television, film and general prop lighting, while keeping its vintage looks and utilizing the modern, readily available 575 W HPL lamp. The 575 W tungsten softlight is formed around a 392 mm sleek, spun parabolic aluminium body which maximizes its curves to look as good on stage as the performers it illuminates. The picklePATT proves that lighting fixtures can be more than just a practical neccessity - the luminaires themselves can be a piece of art and create the mood. The wellknown member of Robe's tungsten classic range - PATT 2013 - has already been used on television broadcasts and concerts worldwide including Jeff Lynne's ELO, Gary Barlow, The Prodigy, Robbie Williams, Paul McCartney, X Factor, Britain's Got Talent, The Graham Norton Show plus numerous other talk-show sets.





High Performance Tungsten Lamp 575 W




N/A



N/A



392 mm parabolic aluminium reflector with high reflectivity coating



Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz



# **Technical Specification**

#### **SOURCE**

- Lamp: High Performance Tungsten Lamp
- Base: G 9,5 special (with heat sink)
- Recommended lamp type: HPL 575/240/X 575W 240V, HPL 575/120/X 575W 120V
- Lifetime: 1500 hours
- Colour temperature: 3050 K

#### OPTICAL SYSTEM

• 392mm parabolic aluminium reflector with high reflectivity coating

#### THERMAL SPECIFICATION

Maximum ambient temperature: 45 °C (113 °F)
Maximum housing temperature: 160 °C (320 °F)

#### **ELECTRICAL SPECIFICATION**

• Input voltage range: 120 V or 240 V, 50/60 Hz

• Power consumption: 575 W

#### MECHANICAL SPECIFICATION

• Height: 520 mm (20.5")

Width: 531 mm (20.9")Depth: 241 mm (9.5")

• Weight: 5.3 kg (11.7 lbs)

• Ingress protection rating: IP20

#### RIGGING

- Mounting points: M12 mounting for clamp or spigot
- Universal operating position

#### **APPROVALS**

- CE Compliant
- cETLus Compliant (pending)

## **INCLUDED ITEMS**

- User Manual
- Power cord

#### **ACCESSORIES**

Lamp HPL575 240V LL: 14080055
Lamp HPL575 120V X: 14080056
Dual Top Loader Case: 10120192



ROBE lighting s .r.o., Hazovice 2090 75661 Roznov pod Radhostem Czech Republic

Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

• Quad Top Loader Case: 10120191

• Floor stand: 10980259 • Tripod: 10980287 • Spigot: 10980260

### **LEGAL**

picklePATT™ is a Trademark of Robe lighting s. r. o.
picklePATT™ is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents